

Supertex

Contact Adhesive



General Description

Supertex is a general purpose contact adhesive, modified form of Supertex to suit almost all types of insulants to metal etc. especially where high stresses are encountered.

It is used as Airconditioning Duct (Adhesive) due to its excellent resistance to water and wet heat. It is used for the attachment of leather, floor carpeting and furniture industry.

Application Instructions:

Type	Flammable, solvent based.
Application	Brush, Scraper, Extruder or Roller.
Coverage	4.5 - 5 sq. Meter/Litre.
Consistency	Brushing.
Non volatile	15 ± 2% by weight.
Colour	White yellowish brown.
Water vapour transmission	Not applicable.
Flammability	Wet - Flammable.
Bonding/Drying Time	1 Sided application 0 - 10 Min. 2 Sided application 5 - 15 Min.
Precautions	Flammable vapour - Avoid naked flames. Ensure good ventilation.
General	Principally used for floor carpeting and furniture industry, ensure good ventilation.
Supply	1 US Gallon, 15 Litres Cans.
Storage life	12 months minimum.

ADHESIVES • DETERGENTS • COATINGS



P.O.Box: 1990 - Safat - 13020 - Kuwait | Tel : (+965) 2471 7010/40 | Fax : (+965) 2472 8519 | info@albahar-industries.com | www.albahar-industries.com

CERTIFIED MANAGEMENT SYSTEM



Made in Kuwait